

The Adjustable Wrist Strap set provides a cost-effective method of grounding personnel. Features a comfortable, adjustable band, a 5 ft. (1.5 m) coil cord with a 4mm snap. One size adjusts to most any size wrist to provide reliable, 360-degree protection. A 1 megohm resistor is built into the ground cord. Adjust band over a range of diameters, 1.7 in. – 3.5 in. Meets ANSI/ESD S20.20 and ANSI/ESD S1.1.

## Wristband

Properties	Typical Value	Test Method	
Fabric	Elastic nylon		
Resistance	< 500 ohms	ANSI/ESD S1.1	
Contact	360 Degrees Around Wrist		
Color	Royal blue with white edgest		
Male Stud Snap	4mm		
Snap Release	< 3 lbs.		
Back Plate	Stainless Steel		

## Coil Cord

Properties	Typical Value	Test Method
Length	5 Feet	
Resistance	1 Megohm	ANSI/ESD S1.1
Flex life average	1,000,000 cycles	ANSI/ESD S1.1
Color	Black	
Female Socket Snap	4mm	

Item	Description
<u>2271</u>	Adjustable Wristband
<u>2272</u>	Adjustable Wrist Strap with 5' Coil Cord

2.	2271/2272 SINGLE-WIRE ADJUSTABLE FABRIC WRIST STRAP			
	926 JR Industrial Drive, Sanford, NC 27332	DRAWING	DATE	
	WEB SITE: <u>StaticControl.com</u>	NUMBER	October	
	PHONE (919) 718-0000	2271/2272	2015	



Note: This product is not recommended for use on equipment with operating voltage exceeding 250 VAC.

CAUTION: The ESD Series is for electrostatic control. It will not reduce or increase your risk of receiving electric shock when using or working on electrical equipment. Follow the same precautions you would use without wrist straps, including:

- Make certain that equipment having a grounding type plug is properly grounded.
- Make certain that you are not in contact with grounded objects other than through the ESD Series.

Unless otherwise noted, tolerance ±10%

Specifications and procedures subject to change without notice.



© 2015 DESCO INDUSTRIES INC. Employee Owned