

This SCS Dual-Wire Fabric Wristband is available in one size that adjusts to almost any size wrist to provide reliable protection. The wristband provides full conductivity, comfort and reliability, while ensuring continuous drain of static charge when used with SCS 2300 Dual-Wire Coil Cords (not included). Made to be used in conjunction with all <u>SCS Workstation Monitors</u>. Meets requirements of ANSI/ESD S20.20 and Wrist Strap standard ANSI/ESD S1.1.

Wristband

Typical Value
Elastic, Nylon
360 degrees around wrist
Light Blue
3.4mm
1 to 5 pounds

Item	Description
<u>2368</u>	Dual-Wire Fabric Wristband

Use with 2300 Series Dual Conductor Coil Cord

ltem	Description	
<u>2360</u>	5ft. (1.5m), Straight	
<u>2370</u>	10ft. (3.0m), Straight	
<u>2371</u>	20ft. (6.1m), Straight	
2360R*	5ft. (1.5m), Right Angle	
<u>2370R</u> *	10ft. (3.0m), Right Angle	
<u>2371R</u> *	20ft. (6.1m), Right Angle	

*To be used with SCS Dual-Wire Monitors only

DUAL-WIRE FABRIC WRISTBAND		
926 JR Industrial Drive, Sanford, NC 27332	DRAWING	DATE
WEB SITE: <u>StaticControl.com</u>	NUMBER	February
PHONE (919) 718-0000	2368	2017



Unless otherwise noted, tolerance ±10%

Specifications and procedures subject to change without notice.

